

# BRAVO HIGH GLOSS MASONRY Sealer

## HAZARD RATING

4=EXTREME  
3=HIGH  
2=MODERATE  
1=SLIGHT  
0=INSIGNIFICANT

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>REACTIVITY</b>	<b>0</b>

## MATERIAL SAFETY DATA SHEET

### GENERAL INFORMATION

**PRODUCT IDENTIFICATION:** BRAVO High Gloss Masonry Sealer

**VOC CONTENT:** 198 GR/LITER OR 1.65 #/GAL.

**CATEGORY:** CURE

**COMMON NAME:** VINYL TOLUENE ACRYLATE EMULSION

#### **DOT SHIPPING NAME:**

IN CONTAINER LESS THAN 119 GALS AND GREATER THAN 119 GALS.  
BRAVO High Gloss Masonry Sealer (NON-REGULATED)

**HEALTH AND SAFETY:** THIS PRODUCT IS AN ORGANIC LIQUID AND WATER EMULSION. PER NFPA 30 THIS MIXTURE WITH A FLASH POINT GREATER THAN 200 F IS A CLASS III B COMBUSTIBLE LIQUID. ALL PRECAUTIONS PROVIDED ARE FOR THE ORGANIC LIQUID PORTION OF WHICH THIS PRODUCT MAY CONTAIN AS LITTLE AS 5%. USE WITH ADEQUATE VENTILATION. DO NOT INDUCE VOMITING IF SWALLOWED. USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE CLOTHING IS ADVISED WHEN HANDLING THIS PRODUCT. KEEP FROM FREEZING.

### SECTION I

**DISTRIBUTOR:** Essroc – Italcementi Group  
**EMERGENCY NO:** 1-800-424-9300 (Chemtrec)  
**ADDRESS:** 3251 Bath Pike, Nazareth, PA 18064  
**PHONE:** 1-800-437-7762 Customer Service (US)  
1-800-386-2111 Customer Service(CAN)  
**PREPARED:** June 4, 2010  
**PREPARED BY:** Essroc MSDS Development Committee

### SECTION II HAZARDOUS INGREDIENTS

<u>MATERIAL OR COMPONENTS</u>	<u>CAS. NO.</u>	<u>%</u>	<u>HAZARD DATA</u>	<u>UN#</u>
VINYL TOLUENE ACRYLATE POLYMER	25085-34-114	25%	ND	
ODORLESS MINERAL SPIRITS EMULSIFIERS	64741-86-76	8%	TLV 100 PPM	1255
		2%	NA	

### SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

**BOILING POINT:** 212° F      **MELTING POINT:** N/A  
**SPECIFIC GRAVITY (H2O=1):** 0.993 VAPOR **PRESSURE:** 2.00 mm Hg VAPOR  
**DENSITY (AIR=1):** GREATER THAN AIR      **SOLUBILITY IN H2O**  
**BY WT:** 100%  
**EVAPORATION RATE (ETHER =1):** 9.5 LESS THAN  
PH (1% SOLN): ND PH (AS IS): 7-8  
**APPEARANCE AND ODOR:** MILKY WHITE EMULSION WITH AROMATIC ODOR (MAY CONTAIN FUGITIVE DYE)

### SECTION IV FIRE AND EXPLOSION HAZARD

**FLASH POINT:** (TEST METHOD) >200° F TCC  
**AUTOIGNITION TEMP:** N.D.  
**FLAMMABLE LIMITS IN AIR, % BY VOL:**      **LOWER:** N.D. **UPPER:** N.D.

**EXTINGUISHING MEDIA:** WATER, FOAM

**SPECIAL FIRE FIGHTING PROCEDURES:** NONE

**UNUSUAL FIRE AND EXPLOSION HAZARD:** PRODUCT WILL BURN IF TEMPERATURE EXCEEDS BOILING POINT WATER MIX. NO UNUSUAL HAZARDS.

### SECTION V REACTIVITY DATA

**CONDITIONS CONTRIBUTING TO INSTABILITY:** THIS PRODUCT IS STABLE

**INCOMPATIBILITY:** THIS PRODUCT IS INCOMPATIBLE WITH STRONG ACIDS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** THERMAL DECOMPOSITION IN THE PRESENCE OF AIR YIELDS CARBON MONOXIDE AND/OR CARBON DIOXIDE.

**CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:** N/A

### SECTION VI HEALTH HAZARD INFORMATION

#### HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE

#### ROUTES OF EXPOSURE:

**INHALATION:** VAPOR INHALATION CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA OR HEADACHE.

**SKIN CONTACT:** PROLONGED OR REPEATED CONTACT CAN RESULT IN MODERATE IRRITATION

**SKIN ABSORPTION:** PROLONGED OR REPEATED CONTACT CAN RESULT IN MODERATE IRRITATION

**EYE CONTACT:** THIS PRODUCT CAN CAUSE SEVERE IRRITATION.

**INGESTION:** CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING.

**EFFECTS OF OVEREXPOSURE:** ANESTHESIA HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.

**ACUTE OVEREXPOSURE:** PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS.

#### EMERGENCY AND FIRST AID PROCEDURES:

**EYES:** FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CONSULT WITH A PHYSICIAN.

**SKIN:** IMMEDIATELY WASH SKIN WITH SOAP AND PLENTY OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

**INHALATION:** REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SEEK PROMPT MEDICAL ATTENTION.

## **SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE**

**WASTE DISPOSAL METHOD:** TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA OR STATE REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT. TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES, INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN UP IS COMPLETE. STOP SPILL AT SOURCE. DIKE SPILL AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

## **SECTION VIII CONTROL MEASURES**

**VENTILATION REQUIREMENTS:** LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY (SPECIFY IN DETAIL):** CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE: FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

**EYE:** CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

**GLOVES:** IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

**OTHER CLOTHING AND EQUIPMENT:** TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

## **SECTION IX SPECIAL PRECAUTIONS**

**PRECAUTIONARY STATEMENTS:** PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER, CLOTHING MUST BE WASHED/DRIED BEFORE RE-USE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

**OTHER HANDLING AND STORAGE REQUIREMENTS:** STORE IN WELL VENTILATED AREA. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

### **HMIS HAZARD RATINGS:**

	NFPA-HMIS	NFPA 704	KEY
HEALTH	1	1	4=SEVERE
FLAMMABILITY	1	1	3=SERIOUS
REACTIVITY	0	0	2=MODERATE
			1=SLIGHT
			0=MINIMAL

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER).

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

## **SECTION X OTHER INFORMATION**

### **Abbreviations:**

ACGIH	American Conference of Government Industrial Hygienists
ASTM	American Society of Testing Materials
CAS	Chemical Abstract Service
CFR	Code of Federal Regulations
DOT	Department of Transportation
IARC	International Agency for Research
IDLH	Immediately dangerous to live and health (NIOSH).
m <sup>3</sup>	cubic meter
mg	Milligram
mm	millimeter
MSDS	Material Safety Data Sheet
MSHA	Mine Safety and Health Administration
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicity Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RQ	Reportable Quantities
SARA	Superfund Amendments and Reauthorization Act
TLV	Threshold Limit Value
TWA	Time Weighted Average
URT	Upper Respiratory Tract
WHMIS	Workplace Hazardous Material Information System

### **Other important information:**

This product should only be used by knowledgeable persons. While the information provided in this material safety data sheet is believed to provide a useful summary of the hazards of this product as it is commonly used, the sheet cannot anticipate and provide all of the information that might be needed in every situation. Inexperienced product users should obtain proper training before using this product.

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY ESSROC – ITALCEMENTI GROUP., except that the product shall conform to contracted specifications. The information provided herein was believed by Essroc to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and

procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach or warranty, negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.